

# 带法兰 齿型惰轮

- L · H型 -

Order 订货示例 型式 (1Type · 2齿数 · 3对应皮带) **RD-SEK-F22L050**

**■中心轴承型**

Type	材质			表面处理
	主体	法兰	轴承	
RD-SEK-F	铝合金	铝合金	钢	本色阳极氧化处理
RD-SKK-F	S45C	SPCC	钢	四氧化三铁保护膜
RD-SDK-F				无电解镀锌

\* 轴承精度JIS B1514 0级(压入前)  
⊕ 轴承采用压入方式。

**■L型**

Type	齿数	对应皮带	轴径 d	P.D.	O.D.	F	E	A	W	S	轴承尺寸			规格有无		
											No.	D	B	RD-SEK-F	RD-SKK-F	RD-SDK-F
铝合金 RD-SEK-F	16	L050	10	48.51	47.75	55	40	14	19	5	6200ZZ×1	30	9	●	●	●
		L075						21	26	8.5				●	●	●
		L100						27	32	6				●	●	●
	18	L050	12	54.57	53.81	61	45	14	19	4.5	6201ZZ×1	32	10	●	●	●
		L075						21	26	8				●	●	●
		L100						27	32	6				●	●	●
铁 RD-SKK-F RD-SDK-F	20	L050	12	60.64	59.88	67	50	14	19	4.5	6201ZZ×1	32	10	●	●	●
		L075						21	26	8				●	●	●
		L100						27	32	6				●	●	●
	22	L050	15	66.7	65.94	80	60	14	19	4	6202ZZ×1	35	11	●	●	●
		L075						21	26	8				●	●	●
		L100						27	32	6				●	●	●
30	L050	15	90.96	90.2	99	80	14	19	4	6202ZZ×1	35	11	●	●	●	
	L075						21	26	8				●	●	●	
	L100						27	32	6				●	●	●	

**■H型**

Type	齿数	对应皮带	轴径 d	P.D.	O.D.	F	E	A	W	S	轴承尺寸			规格有无			
											No.	D	B	RD-SEK-F	RD-SKK-F	RD-SDK-F	
铝合金 RD-SEK-F	14	H075	12	56.6	55.22	61	45	21	26	3	6201ZZ×2	32	10	●	●	●	
		H100						27	32	6				●	●	●	
		H150						40	45	11.5				●	●	●	
		H200						54	59	18.5				●	●	●	
		H075						21	26	3				●	●	●	
		H100						27	32	6				●	●	●	
	16	H075	12	64.68	63.31	70	56	21	26	3	6201ZZ×2	32	10	●	●	●	
		H100						27	32	6				●	●	●	
		H150						40	45	11.5				●	●	●	
		H200						54	59	18.5				●	●	●	
		H075						21	26	4				●	●	●	
		H100						27	32	6				●	●	●	
铁 RD-SKK-F RD-SDK-F	18	H075	15	72.77	71.39	80	60	21	26	4	6002ZZ×2	32	9	●	●	●	
		H100						27	32	6				●	●	●	
		H150						40	45	11.5				●	●	●	
	20	H075	15	80.85	79.48	87	67	21	26	4	6002ZZ×2	32	9	●	●	●	
		H100							27	32				6	●	●	●
		H150							40	45				11.5	●	●	●
22	H075	15	88.94	87.56	95	75	21	26	4	6002ZZ×2	32	9	●	●	●		
	H100							27	32				6	●	●	●	
	H150							40	45				11.5	●	●	●	
24	H075	15	97.02	95.65	104	84	21	26	4	6002ZZ×2	32	9	●	●	●		
	H100							27	32				6	●	●	●	
	H150							40	45				11.5	●	●	●	
25	H075	15	101.06	99.69	111	90	21	26	4	6002ZZ×2	32	9	●	●	●		
	H100							27	32				6	●	●	●	
	H150							40	45				11.5	●	●	●	
28	H075	15	113.19	111.82	123	102	21	26	4	6002ZZ×2	32	9	●	●	●		
	H100							27	32				6	●	●	●	
	H150							40	45				11.5	●	●	●	

指定加工 型式 (1Type · 2齿数 · 3对应皮带) - (FC · NFC · LFC · RFC) **RD-SEK22L050 - NFC**

Alterations Code	法兰切割 FC	不铆接法兰 NFC	仅铆接单侧法兰 LFC · RFC
Spec.	切割法兰, 降低高度。 FC: 指定单位0.5mm ① 法兰外周未进行表面处理。 ② FC ≥ (O. D.) + 2 ③ FC ≤ F - 2 [指定方法] FC65	发货时不铆接法兰。(附带法兰)	发货时仅铆接扣环侧(RFC)或扣环相反侧(LFC)的单侧法兰。(附带1个法兰)



报价确定

Order 订货示例 型式 (1Type · 2齿数) - 3适用皮带 - 4轴径 **RD-SEK-FW20 - L100 - 15**

**■两侧轴承型**

Type	材质			表面处理
	主体	法兰	轴承	
RD-SEK-FW	铝合金	铝合金	钢	本色阳极氧化处理
RD-SKK-FW	S45C	SPCC	钢	四氧化三铁保护膜
RD-SDK-FW				无电解镀锌

\* 轴承精度JIS B1514 0级(压入前)  
⊕ 轴承采用压入方式。

**■L型**

Type	齿数	对应皮带	轴径 d	P.D.	O.D.	F	E	A	W	Dh	轴承尺寸			规格有无			
											No.	D	B	RD-SEK-F	RD-SKK-F	RD-SDK-F	
铝合金 RD-SEK-FW	14	L050	8	42.45	41.68	48	35	14	19	16.5	698ZZ×2	19	6	●	●	●	
		L075						21	26					8.5	●	●	●
		L100						27	32					6	●	●	●
		L150						40	45					11.5	●	●	●
		L050						14	19					4.5	●	●	●
		L075						21	26					8	●	●	●
	15	L050	8	45.48	44.72	48	35	14	19	16.5	698ZZ×2	19	6	●	●	●	
		L075						21	26					8.5	●	●	●
		L100						27	32					6	●	●	●
		L150						40	45					11.5	●	●	●
		L050						14	19					4.5	●	●	●
		L075						21	26					8	●	●	●
16	L050	8	48.51	47.75	55	40	14	19	16.5	698ZZ×2	19	6	●	●	●		
	L075						21	26					8.5	●	●	●	
	L100						27	32					6	●	●	●	
	L150						40	45					11.5	●	●	●	
	L050						14	19					4.5	●	●	●	
	L075						21	26					8	●	●	●	
16	L050	10	48.51	47.75	55	40	14	19	19.5	6900ZZ×2	22	6	●	●	●		
	L075						21	26					8.5	●	●	●	
	L100						27	32					6	●	●	●	
	L150						40	45					11.5	●	●	●	
	L050						14	19					4.5	●	●	●	
	L075						21	26					8	●	●	●	
18	L050	12	54.57	53.81	61	45	14	19	25	6001ZZ×2	28	8	●	●	●		
	L075						21	26					8.5	●	●	●	
	L100						27	32					6	●	●	●	
	L150						40	45					11.5	●	●	●	
	L050						14	19					4.5	●	●	●	
	L075						21	26					8	●	●	●	
20	L050	15	60.64	59.88	67	50	14	19	29	6002ZZ×2	32	9	●	●	●		
	L075						21	26					8.5	●	●	●	
	L100						27	32					6	●	●	●	
	L150						40	45					11.5	●	●	●	
	L050						14	19					4.5	●	●	●	
	L075						21	26					8	●	●	●	
22	L050	15	66.7	65.94	80	60	14	19	29	6002ZZ×2	32	9	●	●	●		
	L075						21	26					8.5	●	●	●	
	L100						27	32					6	●	●	●	
	L150						40	45					11.5	●	●	●	
	L050						14	19					4.5	●	●	●	
	L075						21	26					8	●	●	●	
30	L050	12	90.96	90.2	99	80	14	19	22	6901ZZ×2	24	6	●	●	●		
	L075						21	26					8.5	●	●	●	
	L100						27	32					6	●	●	●	
	L150						40	45					11.5	●	●	●	
	L050						14	19					4.5	●	●	●	
	L075						21	26					8	●	●	●	

**■H型**

Type	齿数	对应皮带	轴径 d	P.D.	O.D.	F	E	A	W	Dh	轴承尺寸			规格有无			
											No.	D	B	RD-SEK-FW	RD-SKK-FW	RD-SDK-FW	
铝合金 RD-SEK-FW	14	H075	12	56.6	55.22	61	45	21	26	27	6201ZZ×2	32	10	●	●	●	
		H100						27	32					6	●	●	●
		H150						40	45					11.5	●	●	●
		H200						54	59					18.5	●	●	●
		H075						21	26					3	●	●	●
		H100						27	32					6	●	●	●
	15	H075	12	60.64	59.27	67	50	21	26	27	6201ZZ×2	32	10	●	●	●	
		H100						27	32					6	●	●	●
		H150						40	45					11.5	●	●	●
		H200						54	59					18.5	●	●	●
		H075						21	26					4	●	●	●
		H100						27	32					6	●	●	●
16	H075	12	64.68	63.31	70	56	21	26	27	6201ZZ×2	32	10	●	●	●		
	H100						27	32					6	●	●	●	
	H150						40	45					11.5	●	●	●	
	H200						54	59					18.5	●	●	●	
	H075						21	26					4	●	●	●	
	H100						27	32					6	●	●	●	
16	H075	15	64.68	63.31	70	56	21	26	29	6002ZZ×2	32	9	●	●	●		
	H100						27	32					6	●	●	●	